


# RONDO2

Rotational LED



**APPLICATION**

Smart Wi-Fi system compatible with Google Home and Amazon Alexa will make your life easier. The app is easy to set up, and can create multiple zones, multiple users and multiple scenes. Available in Tunable White, RGB and RGBW system. Playing with different colors of the LEDs can form infinite color hue possibilities to not only just illuminate space, but manipulate for your desired hue and shades. The Smart Wi-Fi system can provide an ultimate solution to optimize the needs from residential to commercial, healthcare, education, retails, entertainment, office, and more.

**MOUNTING:**

- Pendant.

**ELECTRICAL:**


- High power factor electronic driver, operate from a 120 ~ 277 Vac input range, 50 / 60 Hz.
- Features included over voltage protection, surge, short circuit protection and over load protection.
- Power Factor: typical > 0.95, THD <20, meets Class1 or Class 2 circuit.

**FINISH:**

- Standard powder-coat textured white painted finish on exposed trim, consult factory for custom colors.
- Comes with snap-in acrylic lens as standard.

**LISTING:**

- UL / CUL listed.
- UL listed for dry & damp location.
- Assembled in USA (optional)
- Warranty:  
**Power source:** 5 years limited warranty.  
**-2762K, RGB, RGBW:** 15 years limited warranty.  
**Control:** 2 years limited warranty.



Specifications: RONDO2

Width: 2-1/2 Dia. (63)

All dimensions are in inches (millimeters).

**WEIGHT**

Item	lbs	kg
RONDO2-2	5.08	2.3
RONDO2-3	6.01	2.72
RONDO2-4	6.76	3.06
RONDO2-8	10.88	4.93

# RONDO2

ORDERING INFORMATION

EXAMPLE: RONDO2-IND-4-DLO-2762K-UNV-CV24-SMAFI

MODEL	ROW <sup>1</sup>		SECTION <sup>2</sup>		LED		SYSTEM					
<b>RONDO2-IND</b> (Individual Mount)	<b>xx</b>	Specify nominal overall row length in 1' increments (Continuous runs)	<b>2</b>	2' Length	<b>(Blank)</b>	No Downlight <sup>5</sup>	<b>-2762K</b>	Tunable White 2700-6200K With wireless solution <sup>6,8</sup>				
<b>RONDO2-CON</b> (Continuous Row Mount)									<b>3</b>	3' Length	<b>DLO</b>	Low output, 4.4 W/ft, 494 lm/ft
<b>RONDO2-SQ</b> (Square)									<b>X'x"-Y'y"</b>	Specify dimensions in inches (Minimum required dimensions is 2'4"-2'4", 2' increments), (Straight joint provided over 8ft run in * Must provide a sketch on the last page.	<b>4</b>	4' Length
<b>RONDO2-CM</b> (Custom)	Refer to dimensions page to calculate the total run * Must provide a sketch on the last page.		<b>8</b>	8' Length <sup>3</sup>	<b>(Blank)</b>	No Downlight <sup>5</sup>	<b>RGB</b>	RGB with wireless or Bluetooth solution <sup>6,7</sup>				
			<b>X</b>	Custom Length <sup>4</sup>	<b>DLO</b>	Low output, 4.4W/ft	<b>RGBW-xxK</b>	RGBW with wireless or Bluetooth solution, select white "xxk" in 24/27/30/42/62K <sup>7,9</sup>				
					<b>DHO</b>	High output, 8.8W/ft						
					<b>(Blank)</b>	No Downlight <sup>5</sup>						
					<b>DLO</b>	Low output, 10W/ft						

ANGLE		MOUNTING		VOLTAGE		POWER FEED LOCATION		FINISH	
<b>(Blank)</b>	Down	<b>(Blank)</b>	Pendant	<b>UNV</b>	120-277V	<b>PL</b>	Power location must be provided in the drawing	<b>(Blank)</b>	Matte White
<b>45</b>	45°			<b>120</b>	120V		* Required for -SQ and -CM model only.	<b>BK</b>	Semi-matte Black
<b>90</b>	90°			<b>277</b>	277V			<b>CC</b>	Custom Color
<b>135</b>	135°							<b>CSS</b>	Custom Canopy Color (White is Std.)
<b>180</b>	180°							<b>AMB</b>	Anti-Microbial Coating (Matte Skye White)
									* Non-standard finish with extra charge.

CORD FINISH		CORD LOCATION		CEILING TYPE		SUSPENSION LENGTH		LED DRIVER	
<b>(Blank)</b>	White (Std.)	<b>2DEND</b>	2 Feeds on dual end * Two power feed standard.	<b>X1</b>	T-bar ceiling	<b>AC48</b>	Adjustable Aircraft Cable Canopy 48"L	<b>CV24</b>	24VDC power supply
<b>BKC</b>	Black			<b>X2</b>	Hard ceiling	<b>AC96</b>	Adjustable Aircraft Cable Canopy 96"L		
				<b>X3</b>	Sloped Hard ceiling	<b>ST24</b>	Stem Canopy 24"L		
						<b>ST48</b>	Stem Canopy 48"L		
							* Contact factory for custom length.		

CONTROLS		OPTIONS	
<b>SMAFI</b>	Smart Wi-Fi compatible with Google Home and Amazon Alexa, 24V  * Refer to Table #1-4 to find more information. Shipped separately, field installed. Refer to the installation instructions for more information.	<b>ARRA</b>	Assembled in USA for Buy American Act
		<b>LC</b>	Non-lit 90° coupling
		<b>TC</b>	Non-lit T-shape coupling
		<b>XC</b>	Non-lit X-shape coupling
		<b>LC-VD</b>	Non-lit 90° vertical drop
		<b>LC-BT</b>	Non-lit 90° bottom
		<b>TC-VD</b>	Non-lit T-shape vertical drop

NOTES:

- Specify only when Continuous Row Mount.
- No need to select, if same as row length and section length.
- Comes with 1pc 8ft lens.
- Certain restrictions apply such as wattage and length, please consult with the factory.
- Downlight cover may ship separately depending on the configuration.
- Custom wattage or lumen is not available.
- Refer to RGB chart (Table3) to find more information.
- Refer to Tunable White chart (Table2) to find more information.
- Refer to RGBW chart (Table 4) to find more information.

# RONDO2

**SMAFI (TABLE 1)**



	-2762K (Tunable White)	RGB	RGBW
Input Voltage	24V		
Systems	Google Home, Amazon Alexa		
Dimming Type	PWM		
Dimming Range	5 - 100%		
Signal Type	Wi-Fi		
Operating Frequency	2.4 GHz		
Operating Temperature	-4°F to 113°F (-20°C to 45°C)		
Environment	IP20, indoor / dry location only		
Warranty	2 Years		
App	IOS & Android "Smart Life"		

**TUNABLE WHITE -2762K (TABLE2)**

Tunable Range	2700 - 6200K
Lumen Efficiency	494 lm/ft , up to 108 lm/W
CRI	90+
Dimming	PWM
Color Consistency	3-step MacAdam binning
Lumen Maintenance	> 50,000 hours
Control Options	Wireless remote, Bluetooth (Smartphone / APP)
Warranty	5 years limited warranty for power supply, 15 years limited warranty for LED source

**RGB (TABLE 3)**



Input Voltage	24V
Watt / foot	4.4 W/ft
Lumen / foot	R: 20 lm/ft
	G: 92 lm/ft
	B: 19 lm/ft
Color Consistency	3-step MacAdam binning
Lumen Maintenance	> 50,000 hours
Control Options	Wireless Wall/Desktop remote, Wireless Easy Control remote, Wireless Group/Multi-Zone remote, Bluetooth (Smartphone / APP)
Warranty	5 years limited warranty for power supply, 15 years limited warranty for LED source

**RGBW (TABLE 4)**

Input Voltage	24V
Watt / foot	10 W/ft
Lumen / foot	R: 43.33 lm/ft
	G: 200 lm/ft
	B: 40 lm/ft
	W: 314 lm/ft (24K), 324 lm/ft (27K), 398 lm/ft (30K), 414 lm/ft (42K), 426 lm/ft (62K)
CRI for white LEDs	80+
Color Consistency	3-step MacAdam binning
Lumen Maintenance	> 50,000 hours
Control Options	Wireless Easy control remote, Group / Multi Zone wireless remote, Bluetooth (Smartphone / APP)
Warranty	5 years limited warranty for power supply, 15 years limited warranty for LED source



# RONDO2

\*Fixture can be customized: angle 45°, 90°, 135°, 180° (up light).  
\*Field adjustable using allen key (provided).




\*Compatible with 1/2" pipe stem (provided by others).


# RONDO2




LC




TC




XC




LC-VD



TC-VD





LC-BT





# RONDO2


Rotational LED




All dimensions are in inches (millimeters).



Coupling



Coupling for continuous run




Total run = 97.05 (2465)  
 Calculation: (1245-30)x2+30 = 2460  
 \* Recommended to calculate in mm. for precised measurement.


# RONDO2

**RONDO2-SQ examples (Measurement from center point)**



**2'4"-2'4" (Minimum)**



**10'5.2"-2'4" (Minimum)**



**RONDO2-CM examples (Measurement from center point)**



# ARCHITECTURAL LINEAR

## RONDO2 NON-LIT CONNECTOR PATTERNS

**Instruction:**

- Provide sketches illustrating corner types and overall dimensions.
- Must provide the power location in the drawing.
- Utopia Lighting will decide the optimal fixture combination unless otherwise specified in the drawing

