

TRV

Project Name:	
Type:	



APPLICATION

Specification troffer design with hi-transmission acrylic, high performance static luminaires provide excellent visual control and subtle soft indirect illumination. It is high efficiency, great performance and value make it an ideal choice for commercial and institutional environments.

FEATURES:

- Die formed, cold-rolled, 21-gauge steel construction provides durability and strength.
- Finish in high-gloss baked white enamel over rust inhibiting phosphate coating for maximum corrosion resistance.
- High reflectance white reflector distributes light through both optical elements.
- Unique door frame design delivers a premium extruded appearance.
- Smooth edges for easy handling.
- Door latches and hinges from either side as standard.

SHIELDING:

- Two slope panels of the units are high transmission acrylic that provide a low-brightness glow.

MOUNTING:

- Recessed mounted in expose T-bar ceilings, Internal T-bar safety clips.
- Field installed flange kits are available.

LAMP:

- Standard T5, T5HO or PL-L lamps available.
- Pressure-lock lamp holders or easy twist lock lamp sockets.
- Lamps not included.

ELECTRICAL:


- High power factor programmed start electronic ballast for T5 and T5HO lamps are sound rate A, minimum starting temperature 0°F (-18°C), <10% THD and input voltage ranges of 120 to 277 volts comes as standard.
- Ballast disconnect plug provided as standard.

LISTING:

- UL/CUL listed and labeled.
- Suitable for damp locations.
- ARRA compliant.
- Made in USA.

CONFIGURATIONS

Series	Size	# Of Lamps	Lamp Type
TRV	2'x2'	2	14T5, 24T5HO, CF40
	2'x4'	2	28T5, 32T8, 54T5HO



Specifications: 2'x2'

Length: 23-3/4 (603)
Width: 23-15/16 (608)
Depth: 3-3/4 (95.3)

Specifications: 2'x4'

Length: 47-3/4 (1213)
Width: 23-15/16 (608)
Depth: 3-3/4 (95.3)

All dimensions are in inches (millimeters).

ORDERING INFORMATION

EXAMPLE: TRV-22-2-14T5-UNV

MODEL	SIZE	# OF LAMPS	LAMP TYPE	TRIM TYPE	BALLAST
TRV	22 2'x2'	2	14T5 F14T5 (22")	(Blank) Grid Flange ¹	(Blank) T8 Electronic Ballast, Instant Start, <10% THD or T5 Electronic Ballast, Programmed Start, <10% THD
	24 2'x4'		28T5 F28T5 (46")		
			17 F17T8 (24")		HPS Electronic Ballast, Programmed Start, High Light Output, <10% THD
			32 F32T8 (48")		
			24T5HO F24T5HO (22")		
			54T5HO F54T5HO (46")		

VOLTAGE		OPTIONS	
UNV	120-277V (Std.)	AB	Two Ballast for AB Switch
120	120V	EM	Emergency Ballast ²
277	277V	EMC	CEC compliant EM ⁵
347	347V	DM	Dimming Ballast ³
		GLR	Fast Blow Fuse ⁴
		GMF	Slow Blow Fuse ⁴
		MS11	Master Slave w/ 11' Whip
		PW6	Pre-wired 6' Whip Flex #18/3

NOTES:

1. Flange kits are supplied in separate boxes, field installed.
2. Emergency Ballast options, see page 390.
3. Dimming Ballast options, see page 391.
4. Must specify voltage, not available with 347V.
5. Check with factory for more details.